



Antifreeze

ANTIFREEZE / SUMMER COOLANT

EcoTech Lubricants

ANTIFREEZE CONCENTRATE 95%

DESCRIPTION:

Antifreeze / summer coolant is a blend of M.E.G and wide range of corrosion inhibitors, for maximum protection mixed with 50% of water, it will lubricate the water pump, provides protection against extreme temperatures. Can be used in cooling system of petrol and diesel engines, particularly those incorporating aluminium alloys up to - 36°C

APPLICATION:

- Automotive
- Construction
- Earthmoving, quarrying and mining
- Agricultural Equipment

BENEFITS:

- Silicate free type inhibitor system provides exceptional protection.
- Protects all engines, cooling systems, and metals such as iron, steel, aluminium, copper and solder alloys against corrosion.

PERFORMANCE LEVELS

MEETS OR EXCEEDS:

MB 325.0 ASTM D330
SABS 1251 SAE J1034

RECOMMENDED MIXTURE RATIOS:

25% Dilution -12 °C
33% Dilution -18 °C
50% Dilution -36.5 °C

TYPICAL PHYSICAL CHARACTERISTICS	SAE 15W40
Colour ASTM	Blue
Density, KG/L @ 20°C	1.133
Equilibrium Boiling Pt. (undiluted)°C	170
Freezing Pt (50 Vol% Solution)°C	-36.5
Reserve Alkalinity ml 0,1N HCL Ph., 50 Vol% Solution	7
	15